


(SUBMIT IN TRIPLICATE)

Land Office

Lease No.

Unit

LM 04063



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

1963 JUL 29 AM 10:39

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA.)

July 19, 1963

Well No. **1-10** is located **1980** ft. from **N** line and **1980** ft. from **W** line of sec. **10**
NW/4 of Section 10 **T-20-S** **R-34-E** **N. M. P. M.**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (M. L. or P. M.)
Wilcox **Lee County** **New Mexico**
 (Field) (County) (State or Territory)

The elevation of the derrick floor above sea level is **5549.9** ft.

DETAILS OF WORK

State names of and expected depths to objective sands, show sizes, weights, and lengths of proposed casings. Indicate sanding jobs, cementing points, and all other important proposed work.

7/19/63: Pits filled, location cleaned, and marker set.

Cement plug from 3150 to 3250 w/30 sxs cement.
 Cement plug from 1850 to 1950 w/30 sxs cement.
 Cement plug from 1560 to 1610 w/15 sxs cement.
 Cement plug from 200 to 250 w/20 sxs cement.
 15 sxs. top of surface pipe.
 Mud placed between all plugs.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Greathouse, Pierce & Davis**
 Address **207 Midland Savings Bldg.**
Midland, Texas

[Signature]
 Title