

HOBBS OFFICE O.G.C.
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 9 7 45 AM '67

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT..." (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 7. Unit Agreement Name |
| 2. Name of Operator Martin Yates, III | 8. Farm or Lease Name Bilbrey |
| 3. Address of Operator 323 Carper Building, Artesia, New Mexico. | 9. Well No. 1 |
| 4. Location of Well UNIT LETTER <u>I</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>760</u> FEET FROM THE <u>East</u> LINE, SECTION <u>19</u> TOWNSHIP <u>19 S.</u> RANGE <u>38 E.</u> NMPM. | 10. Field and Pool, or Wildcat Wildcat |
| 15. Elevation (Show whether DF, RT, GR, etc.) 3592.3 Ground level. | 12. County Lea |

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

| | | | |
|--|---|---|--|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input checked="" type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOB <input type="checkbox"/> | |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled 2530' of 5½" casing. Filled hole with heavy mud and spotted cement plugs as follows: 25 sack plug across and above perforation from 4176' to 4431'. 25 sack plug in top of stub of 5½" casing at 2530'. 25 sack plug at top of salt at 1756'. 25 sack cement plug at bottom of 8 5/8" casing at 325'. Set regulation marker in 10 sack cement plug at surface. Plugging operations completed December 20, 1966. Filled pits and cleaned location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *M. L. Coates* TITLE Bookkeeper DATE 1-6-67

APPROVED BY *Lashie A. Clements* TITLE OIL & GAS SUPERVISOR DATE _____

CONDITIONS OF APPROVAL, IF ANY: