

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE C. C. G.
NEW MEXICO OIL CONSERVATION COMMISSION
JAN 7 1 31 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> 2. Name of Operator Martin Yates, III 3. Address of Operator 323 Carper Building, Artesia, New Mexico. 4. Location of Well UNIT LETTER I , 1980 FEET FROM THE South LINE AND 760 FEET FROM THE East LINE, SECTION 19 TOWNSHIP 19 S. RANGE 38 E. NMPM.	7. Unit Agreement Name 8. Farm or Lease Name Bilbrey 9. Well No. 1 10. Field and Pool, or Wildcat Wildcat 12. County Lea
15. Elevation (Show whether DF, RT, GR, etc.) 3592.3 Ground level.	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to pull as much 5½" casing as possible. Plan to plug and abandon as follows:
Fill hole with drilling mud. Spot 25 sack cement plug across and above perforations. Spot 25 sack cement plug in top of 5½" stub. Spot 25 sack cement plug at top of salt, and 25 sack cement plug at bottom of 8 5/8" casing. Set regulation marker in 10 sack plug at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Martin Yates* TITLE **Bookkeeper** DATE **1-5-66**

APPROVED BY *[Signature]* TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: