

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-1151

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER DRY

2. NAME OF OPERATOR

CONTINENTAL OIL CO.

3. ADDRESS OF OPERATOR

P.O. BOX 460 HOBBS, N. MEX.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL + 1980' FEL OF SEC. 10

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SANDERSON R-1

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 10 T-205, R-36E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3581' DF

12. COUNTY OR PARISH

LEA

13. STATE

N. MEX.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

This well was plugged & abandoned by the following
procedure.

Cut 7 7/8" casing at 2510' & pulled. Set a 50 sk. cmt
plug at 2524, a 35 sk cmt plug at 1350' and a 50 sk
plug around 10 7/8 casing shoe at 405'. Placed a 10 sk plug
at surface and capped well with dry hole marker. Mud
was placed between each cmt plug. Location has been cleaned
and is ready for inspection. Work was started and completed
on 11-17-71.

USGS-HOBBS 5, NMFO PTRS. FILE

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE ADM. SUPERVISOR

DATE 11-22-71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

MAR 3 1972

*See Instructions on Reverse Side

J. A. GORDON
ACTING DISTRICT ENGINEER