

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRORATION OFFICE	
OPERATOR	

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE If State Land submit 6 Copies

Pan American Petroleum Corporation
(Company or Operator)

State "A" Tr. 6

AREA 640 ACRES
LOCATE WELL CORRECTLY

Well No. 2, in NW 1/4 of SW 1/4, of Sec. 15, T. 19S, R. 30E, NMPM.
Fobbs Pool, Ler. County.
Well is 350 feet from North line and 660 feet from East line
of Section 15. If State Land the Oil and Gas Lease No. is 33344.
Drilling Commenced 5-14-63, 19. Drilling was Completed 5-22-63, 19.
Name of Drilling Contractor Cactus Drilling Company
Address San Angelo, Texas
Elevation above sea level at Top of Tubing Head 3613' BGS. The information given is to be kept confidential until
Not Confidential, 19.

OIL SANDS OR ZONES

No. 1, from 4065 to 4119 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	24	New	422	Guide			Surface
4-1/2"	9.5	New	4343	Guide		4065-4119	Oil string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8"	430	250	Pump-Plug		
7-7/8"	4-1/2"	4130	300	Pump-Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforations 4065-4119' acidized with 500 gallons and fraced with 30,000 gal oil and 15,000# sand.
Result of Production Stimulation Pmp 46 BO x 0 BW 24 hr
Depth Cleaned Out 4222'

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 4130 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 6-14-63, 19
OIL WELL: The production during the first 24 hours was 46 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 36°
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1572		T. Devonian		T. Ojo Alamo
T. Salt	1678		T. Silurian		T. Kirtland-Fruitland
B. Salt	2714		T. Montoya		T. Farmington
T. Yates	2752		T. Simpson		T. Pictured Cliffs
T. 7 Rivers	2987		T. McKee		T. Menefee
T. Queen	3526		T. Ellenburger		T. Point Lookout
T. Grayburg	4020		T. Gr. Wash		T. Mancos
T. San Andres			T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	190	190	Caliche, Sand				
190	1580	1390	Red Bed				
1580	1680	100	Anhy				
1680	2130	450	Anhy-Salt				
2130	2610	480	Salt				
2610	3172	562	Anhy, Salt				
3172	3860	688	Anhy				
3860	3996	106	Dolo				
3996	4078	32	Anhy, Lime				
4078	4130	52	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Pan American Petroleum Corp. Address Box 68 - Hobbs, New Mexico
Name Position or Title Area Superintendent
Date June 18, 1963