



© Copyright. Reproduction Prohibited

STATE NM

API 30-025-20539

MAP

COORD

7-2-20 NM

Re SPD 7-26-79 Re CMP 5-4-83

CSG

WELL CLASS:	INIT	DX	FIN	DO	LSE.	CODE
-------------	------	----	-----	----	------	------

8 5/8-430-225 sx

FORMATION

DATUM

FORMATION

DATUM

4 1/2-4130-600 sx

2 3/8-4095

ID	4228	(SADR)
----	------	--------

PRD

IP (Grayburg-San Andres) Perfs 4065-4119 P 7 BOPD + 35 BW.

Pot based on 24 hr test. GOR TSTM; gty (NR)

(CONTR

OPRS ELEV

3614 DF

SUR'S

F.R.C. 7-13-85 OWDD

PD 4228 RT

(Orig. Pan American Pet, #2 State "A" Tr. 9,
Cmp. 6-15-63 thru(Grayburg) Perfs 4065-4119,
OTD 4130, OPB 4122)

7-8-85

TD 4228; Complete

Deepened to 4130 to 4228

Acid (4065-4228) 5000 gals (15% NE HCL)

Ppd 3 BO + 328 BW + 24 MCFG in 24 hrs (4065-4228)

CIBP @ 4121

7-13-85

COMPLETION ISSUED

7-2-20 NM

IC 30-025-70335-85

7-1-63 F.R. 5-23-63, Grayburg. Oper's Elev. 3613'
AMENDED Lease Designation: was State "A"
Tr. 9
PD 4200', Cactus Drlg. Co. - Contractor.

7-1-63

COUNTY	Lea	FIELD	Hobbs	STATE	N.M.	NO.	
OPR.	Pan American Petroleum Corporation					MAP	
NO.	2	LSE	State "A" Tr. 9				
SEC.	15	T.	19S	BLK. R	38E	SUR.	CO-ORD.
LOC.	350' fr N Line & 660' fr W Line of Sec.						
MI.	FROM		CLASS.		EL 3612' E		
SPUD.	5-14-63	COMP.	6-15-63	FORMATION	DATUM	FORMATION	DATUM
TRT.	500 MA, SOF 30,000			LOG:			
	Gals			Yates	2751		
CSG. & SX.				Queen	3513		
	8 5/8"	430'	225	Penr	3628		
	4 1/2"	4130'		Gryb	4065		
TBG.	DEPTH	SIZE					
LOGS	EL	GR	RA	IND	HC	A	
				TD	4130'	PB	4122'
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.
4065-4119'	Pump 46 BO	0		1385	36.		
(Grayburg)							
HRS. TEST							
24'							
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT.	Cactus Drlg. Co.			PROP DEPTH	4200'	TYPE	
DATE							

F.R. 5-23-63, Grayburg. Oper's Elev. 3613'.
 PD 4200' - Contractor Cactus Drlg. Co.
 5-21-63 Drlg. 4068'.
 5-27-63 TD 4130', PB 4122', prep to perf.
 6-3-63 TD 4130', PB 4122', prep to RU Pump.
 Perf 6/4065-68', 6/4074-77', 6/4083-86', 6/4096-99',
 6/4103-06', 6/4112-15', 6/4116-19', Treated 500 MA,
 SOF 30,000 gals.
 Swbd 72 BLO in 5 hrs. (-737)
 6-10-63 TD 4130', PB 4122', ppg. load.
 Ppd. 206 BLO in 72 hrs. (-229).
 6-17-63 TD 4130', PB 4122', COMPLETED.
 Rec load. (Holding for tops).
 6-24-63 TD 4130', PB 4122', Completion Reported.