

|                                          |                      |                |            |
|------------------------------------------|----------------------|----------------|------------|
| COUNTY                                   | LEA                  | FIELD Monument | STATE N.M. |
| OPR                                      | GULF OIL CORPORATION |                | MAP        |
| 9 Whitmire, Bertie                       |                      |                |            |
| Sec. 8, T-20-S, R-37-E                   |                      |                | CO-ORD     |
| 1980' fr N Line & 330' fr E Line of Sec. |                      |                |            |
| Spud 7-9-64                              |                      | CLASS          | EL 3559'   |
| Comp 9-4-64                              |                      | FORMATION      | DATUM      |
| CSG & SX - TUBING                        |                      | LOG:           |            |
| 9 5/8"                                   | 1136'                | 550            | Anhy 1092  |
| 7"                                       | 3844'                | 800            | Yates 2470 |
|                                          |                      |                | 7-R 2834   |
|                                          |                      |                | Queen 3203 |
|                                          |                      |                | Penr. 3302 |
|                                          |                      |                | Grb. 3500  |
| LOGS EL GR RA IND HC A                   | TD 3845', PBD 3770'  |                |            |

IP Grayburg Perfs. 3715-65', Flwd. 1854 MCFGPD +  $\frac{1}{2}$  BW. Pot.  
Based on 24 hr. test thru 26/64" chk., TP 500#.

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

|       |                               |            |       |      |
|-------|-------------------------------|------------|-------|------|
| CONT. | Moran Oil Prod. & Drlg. Corp. | PROP DEPTH | 3900' | TYPE |
| DATE  |                               |            |       |      |

F. R. 5-7-64.  
PD 3900' - San Andres.  
Contractor - Moran Oil Prod. & Drlg. Corp.  
7-13-64 Drlg. 2270' anhy & salt.  
7-20-64 Drlg. 3566'.  
7-27-64 TD 3845', PB 3833', WOC.  
Perf. 3811-16' w/2 SPF.  
Ac. 250 gals.  
Swbd. 100% wtr.  
Sq. 3811-16' w/100 sx.  
Perf. 3779-81', 3789-91 w/2 SPF.  
Ac. 250 gals., swbd. dry.  
Re-Ac. 1000 gals.  
Swbd. 100% wtr.  
Sq. 3779-91' w/200 sx.  
8-3-64 TD 3845', PBD 3833', SI.  
Perf. 3715-17', 3731-33', 3743-45', 3756-58' &  
3763-65' w/2 SPF.

8-3-64 - cont'd -

Ac. 500 gals. (MA).

Swbd. 5 BO/no time.

Flwd. 1845 MCFGPD + 1/2 BW thru 26/64" chk.,

TP 500#, (-150 BLO).

8-10-64 TD 3845', PB 3833', SI.

8-17-64 TD 3845', PB 3770' (Corr) tstg.

Re-Ac. 500 gals. 3756-65'.

Flow 77 BLO + 33 BW/24 hrs. thru 26/64" chk.,

TP 250#, CP 610#.

8-24-64 TD 3845', PB 3770', flg. load.

Flow 4 1/2 BLO + 163 BW/72 hrs. thru 30/64" chk.

8-31-64 TD 3845', PB 3770', flg. load.

Flow 1 BLO + 108 BW/48 hrs. thru 30/64" chk.,

9-8-64 TP 200#, CP 580#, Gas Vol. 1114 MCFGPD.  
TD 3845', PBD 3770', COMPLETED.