

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION
Mar 7 7 50 AM '66

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
Singleton	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Lynch Extension	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Dry
2. Name of Operator
William A. & Edward R. Hudson
3. Address of Operator
302 Carper Building, Artesia, New Mexico
4. Location of Well
UNIT LETTER D , 990 FEET FROM THE West LINE AND 990 FEET FROM THE North LINE, SECTION 28 TOWNSHIP 20S RANGE 34E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3690 D.F.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On February 20, 1966, verbal approval was obtained by Mr. Joe Ramey to plug well as follows: Plugged back with rocks and lead wool from 3721 to 3708. Bailed hole dry (water shut-off). Shot off 7" casing at 3472'. On Feb. 21, plugged back with cement from 3708-3433', mud from 3433 to 3300' and cement from 3300 to 1500', mud from 1500' to 950', cement from 950' to 850' and mud to 10'. Cemented 10' at surface. 10-3/4" and 8-5/8" casing strings were pulled. Used 622 sacks of cement. A 4" x 10' pipe marker has been placed at surface. Location has been cleaned and is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ralph L Gray TITLE Consulting Engineer. DATE March 3, 1966

APPROVED BY John W. Rungan TITLE _____ DATE _____

CONDITION OF APPROVAL, IF ANY: