

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NOV 24 2 02 PM '65
HOBBS OFFICE N. M. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
State - E-8072	
7. Unit Agreement Name	
NONE	
8. Farm or Lease Name	
State New Mexico "DB"	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Osudo Morrow	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>	2. Name of Operator
	TEXACO Inc.
3. Address of Operator	P. O. Box 728 - Hobbs, New Mexico
4. Location of Well	
UNIT LETTER B 710 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 25 TOWNSHIP 20-S RANGE 35-E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	Not Available

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 396'
Spudded 15" Hole at 11:00 P. M. November 22, 1965

Ran 374' of 11 3/4" O. D. Casing, 23.72 LB, Spiral Weld, NEW, and cemented at 396' with 350 Sx. Incorporated with 2% CACL. Plug at 371'. Cement Circulated.

Temperature of mixing slurry - 94°, Strength 12 Hours - 1000 P. S. I.
Bottom Hole Temperature - 62°, Job complete 12:30 P. M. November 23, 1965.

Tested 11 3/4" O. D. Casing for 30 minutes with 600 P. S. I. from 12:30 A. M. to 1:00 A. M. November 24, 1965. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 2:00 A. M. to 2:30 A. M. November 24, 1965. Tested O. K. Job complete 2:30 A. M. November 24, 1965.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Dan Gillett</u>	TITLE <u>Assistant District Superintendent</u>	DATE <u>November 24, 1965</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>[Signature]</u>	DATE <u>[Signature]</u>

CONDITIONS OF APPROVAL, IF ANY: