

NEW MEXICO OIL CONSERVATION COMMISSION Form C-103 (Continued) Date 3-17-66.

Sinclair Oil & Gas Company

P. O. Box 1920, Hobbs, New Mexico

Lea 373 "A" - Well No. 1, Unit Ltr I, 1980' from So. and 660' from East, Section 34-T19S-R37E
Lea County, New Mexico.

- 2-20-66 Jet perforated Tubbs 6505-20-24-27-49-58-66-77-92-97-6607-11-13-21-25' w/30 - 3/8" holes.
- 2-21-66 Spot 120 gals. MA over perfs. 6505-6625'. Set packer @ 6440' and M.A. washed Tubbs perforations w/total of 1400 gals. M.A. & 42 ball sealers Max. Press. 3800#, Min. 2600# @ 4 BPM. Good ball action, Inst. SIP 2600#, 10 mins. WIP 2400#.
- 2-22-66 Sand Oil Frac Tubbs perfs. 6505-6625' w/20000 gals. refined oil plus 20000# sand and 500# Adomite w/28 ball sealers. Max. Press 7000#, Min. 5800# @ 11.1 BPM. Inst. SIP 3400#, 10 mins. SIP 3200#. 12 hr. SITP 2000#. Flow Tubbs perfs. 6505-6625' 175 BLO in 20 hrs. and died. 20/64" choke. Tbg Press. 0 to 50#.
- 3-15-66 Pumped Tubbs perfs. 6505-6625' 10 BLO plus 9 BNO Gravity 37.5.
- 3-16-66 On 24 hr. potential test ending 6:00 PM 3-16-66 pumped Tubbs perfs. 6505-6625' 25 BNO, gravity 37.5 plus 4 BLW. GOR 125:1.