

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well, and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

FEB 27 1 19 PM '67

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 867	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 1006	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____ 2273	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2430	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____ 2577	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. *Tansill 2316	T. Chinle _____	T. _____
T. Penn. _____	T. *Ocatillo 2347	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	15	15	Caliche				
15	30	15	Sand				
30	65	35	Sand and shale				
65	80	15	Water sand (2 Blr's/hr)				
80	90	10	Gravel				
90	135	45	Sand				
135	260	125	Red shale				
260	325	65	Sand (16 Blr's/hr)				
325	340	15	Red shale				
340	390	50	Blue-gy shale				
390	867	477	Red shale				
867	1006	139	Anhy w/ red shale				
1006	2263	1257	Salt				
2263	2317	54	Anhydrite				
2317	2342	25	Dolomite				
2342	2365	23	Sand and Dolomite				
2365	2427	62	Dolomite				
2427	2468	41	Sand w/ some dolomite				
2468	2494	26	Dolomite				
2494	2518	24	Sand w/ some dolomite				
2518	2566	48	Dolomite				
2566	2573	7	Sand and dolomite				
2573	2581	8	Dolomite				
2581	2588	7	Seven Rivers Reef dolomite with porosity. (1600' of oil in hole).				