

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. MI-055043
2. NAME OF OPERATOR Getty Oil Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 249, Hobbs, New Mexico 88240	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 590' PSL, 1913' FWL Unit #	8. FARM OR LEASE NAME
14. PERMIT NO.	9. WELL NO. 2
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3653.6' Gr.	10. FIELD AND POOL, OR WILDCAT
	11. SECTION, T., R., OR BLK. AND SURVEY OR AREA Section 19, T.2S, R.34E
	12. COUNTY OR PARISH 13. STATE Lon N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 3492' TD. Set 5-1/2" 15.5# J-55 3R casing at 3486'. DV tool at 3086'. Bottom 261' Buff-cased and covered w/scrubbers and centralizers. Cemented first stage with 120 sz Class "C" with 2% CaCl₂. Circ. an estimated 35 sz cement. Cemented 2nd stage with 380 sz Class "T" with 4% gel, 33% salt per sack and 1% CaCl₂. Temperature survey indicated top of cement behind 5-1/2" 800' from surface. Released rig at 9:00 PM 5-11-69.

Rigged up X-Port Well Service 5-14-69, drilled cement from 3043-3086'. Tested casing with 1000# for 30 minutes, no drop in pressure. Drilled DV tool. Tested casing at 1000# for 30 minutes, no drop in pressure.

18. I hereby certify that the foregoing is true and correct

SIGNED **C. L. Wade**

TITLE **Area Superintendent**

DATE **5-16-69**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

MAY 19 1969

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.