

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.T.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
E-8184

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FCM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name W. Pearl Queen Unit
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name
3. Address of Operator P. O. Box 670, Hobbs, NM 88240	9. Well No. 166
4. Location of Well UNIT LETTER 0, 105 FEET FROM THE South LINE AND 1325 FEET FROM THE East LINE, SECTION 28 TOWNSHIP 19S RANGE 35E NMPM.	10. Field and Pool, or Wildcat Pearl Queen
15. Elevation (Show whether DF, RT, GR, etc.) 3703' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

POH with production equipment. Set CIBP at 4615'. Found hole between 2171' & 2174'. Circulate hole with abandonment mud. Spot 35' cement on CIBP. Spot 100' plug 2900'-3000'. Set cement retainer at 2102'. Pumped 35 sacks Class "C" into hole in casing 2171'. Circulate hole with abandonment mud to surface. Perf 1875' with (4) ½" JH with 90° phasing. Pump into perf (did not circ). Set cement retainer at 1822'. Pump 425 sacks Class "H" cement with 16% gel followed by 100 sacks Class "C" (did not circ). Run temperature survey, found top of cement at 1809'. Perf 381' with (4) ½" JHPF. Pump thru perf, circulate to surface. Pump 125 sacks Class "C", circulate to surface. Install dry hole marker, clear and clean location. P&A complete 2-8-81.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. D. Pitzer TITLE Area Engineer DATE 2-23-81

APPROVED BY [Signature] TITLE [Signature] DATE [Signature]

CONDITIONS OF APPROVAL, IF ANY: