

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions
on reverse side)

DATE: August 31, 1984
B. LAND DESIGNATION AND SERIAL NO.
NM-02127-A

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. NAME OF OPERATOR Arlen L Edgar		2. ADDRESS OF OPERATOR 208 HBF Bldg. Midland, Texas 79701		3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below) At surface NE/4 NW/4 Section 35 660/N + 1980/W T-20-S R-34-E Lea County, New Mexico		4. PERMIT NO.		5. REMARKS (E.g., whether DP, WT, etc.)		6. COUNTY OR PARISH Lea		7. STATE N. Mexico			
OIL WELL ☒ GAS WELL ☐ OTHER ☐		AUG 10 2 43 PM '89		8. NAME OF LEASE Federal C		9. WELL NO. 1		10. FIELD AND POOL, OR WILDCAT Lynch (Yates-7 Rivers)		11. SEC. T. R. M. OR B.M. AND SURVEY OR AREA 35 T-20-S R-34-E		12. COUNTY OR PARISH Lea		13. STATE N. Mexico	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETS	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☒
REPAIR WELL	☐	CHANGE PLANE	☐
(Other)	☐		

SUBSEQUENT REMOVAL OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other)	☐		

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

The Federal C was drilled by Penzoil United in 1970. It was plugged and abandoned. It was re-entered by Arlen Edgar in 1974 with a plug back depth of 3750. The casing left in the well was 20" @ 30' 13 3/8 @ 866' cmt w/ 900 ska., 9 5/8" @ 5600 cmt. top @ 1950. Perforations are from 3577 to 3708. The well was acidized, fraced and completed pumping for 11 BOPD and 6 BWPD in August 1974. In November 1974 it was discovered that the casing had parted at 2402.

Approval is requested to plug and abandon the well as follows.

1. Run in hole with 8" impression block.
2. If image on block indicates we can get into parted casing, pick up bent joint of tubing and attempt to enter parted casing and run tubing to 3577. If successful pump 35 sacks of class C cement. If unsuccessful in attempt to enter parted casing, set 9 5/8" retainer on tubing at 2350' and pump 15 sacks of class C cmt. below retainer. Dump 10' of cmt. on retainer.
3. Perforate 9 5/8" casing at 900'. Set retainer at 800'. Pump 100 ska. of class C. Dump 10' of cmt. on retainer.
4. Set 10' of cmt. in top of 9 5/8" casing with marker.

changes as per B.M. Manus/S.J. Shaw &
Bernard Lankford. (SJS) 8/10/89

18. I hereby certify that the foregoing is true and correct

SIGNED B.R. Lankford

TITLE Agent

DATE 7-2-89

(This space for Federal or State office use)

APPROVED BY Shannon Shaw
CONDITIONS OF APPROVAL, IF ANY:

FOR: Shannon Shaw
TITLE

DATE 8-15-89

*See Instructions on Reverse Side