Form	9-331
(May	1963)

UNI D STATES DEPARTMEN. OF THE INTERIOR (Other Instructions verse side)

SUBMIT IN TRIPLY

75.0

FEDERAL NM 02127A

Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY

ď.	IF	INDIAN,	ALLOTTEE	OR	TRIBE	NAME

	(Do not use this form for propos	ICES AND REPORTS cals to drill or to deepen or plus arrive for BERMIT—" for such	hack to a different magazzata		DOTTED ON THISE NAME	
1.	OIL X GAS OTHER			7. UNIT AGREEME	NT NAME	
2.	2. NAME OF OFERATOR ARLEN L. EDGAR				8. FARM OR LEASE NAME FEDERAL "C"	
3.		ULF BUILDING, MIDLA		9. WELL NO.		
4.	 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 			LYNCH (7 R	IVERS - YATES	
14	UNIT LETTER C	1980' FWL & 660' FN		SURVEY OR		
	PERMIT NO.	15. ELEVATIONS (Show whether 3734.7 GR	DF, RT, GR, etc.)	12. COUNTY OR P. LEA	N.M.	
16.	Check Ap	propriate Box To Indicate	Nature of Notice, Report, o	or Other Data		
	NOTICE OF INTENTION TO:			SEQUENT REPORT OF:		
	FRACTURE TREAT M	ULL OR ALTER CASING ULTIPLE COMPLETE BANDON* HANGE PLANS	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) RE-ENTRY (NOTE: Report res	X ALTERI ABANDO OF P&A WELL sults of multiple comple	ING WELL NG CASING NMENT* tion on Well	
17.	DESCRIBE PROPOSED OR COMPLETED OPER proposed work. If well is direction	ATIONS (Clearly state all pertine				

locations and measured and true vertical depths for all markers and zones perti-

COMMENCED 5/18/74 - RU WELL SERVICE UNIT, DRILLED OUT CEMENT PLUGS AND CIRCULATED HOLE CLEAN TO 3897. SPOTTED 500 GAL. 15%NE AND PERFORATED 7 RIVERS REEF FROM 3762. - 66. WITH/2 SPF. DISPLACED ACID AND SWABBED MUD. SQUEEZED PERFORATIONS 3762 -66 WITH 200 SX. DRILLED OUT TO 3840 . SPOTTED 500 GALS. 15% NE AND RE-PERFORATED 7 RIVERS REEF AT 3760 -68 WITH/2SPF. DISPLACED ACID AND SWABBED TOTAL OF 114 BBLS. LOAD AND FORMATION WATER WITH/TRACE OIL AND GAS. SQUEEZED PERFORATIONS 3760 -68 WITH/150 SX. DRILLED CEMENT TO 3750'. SPOTTED 500 GALLONS 15% NE AND PERFORATED YATES SANDS WITH/1SPF FROM 3577-70, 3588-98, 3603-10, 3640-54, 3702-08, TOTAL 39 SHOTS. SWABBED LOAD WATER AND OIL AND SWABBED DRY. RE-ACIDIZED WITH/1500 GALLONS 15% NE. SWABBED LOAD AND OIL. FRAC/20,000 GALLONS TREATED FRESH WATER AND 20,000 LBS. SAND. BUILT TANK BATTERY, INSTALLED PUMPING UNIT AND RAN RODS AND PUMP. TOP YATES 3523. TOP 7 RIVERS REEF 3760.

8. I hereby certify that the foregoing is true and correct				
SIGNED Aven I. Edgar	TITLE _	OWNER		DATE 9/9/74
(This space for Federal or State office use)				
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE _			DATE