

3-27-72 TD 10,416'; PBD 10,381'; SI
 Swbd 3 BO + 25 BW in 7 hrs (10,088-100')
4-3-72 TD 10,416'; PBD 6516'; WOC
 Pulled 5 1/2" & Re-Ran to 6516'
4-10-72 TD 10,416'; PBD 6468'; SI
 Perf 6390-94' w/1 SPF
 Acid (6390-94') 1000 gals
 Swbd 90 BW in 24 hrs (6390-94')
 BP @ 6345'
 Perf 6242-46' w/4 SPF
 Acid (6242-46') 1000 gals (15%)
 Swbd 69 BW in 24 hrs (6242-46')
 BP @ 6210'
 Perf 6160-64' w/4 SPF

4-10-72 Continued
 Acid (6160-64') 1000 gals (15%)
 Swbd 60 BFW in 12 hrs (6160-64')
4-17-72 TD 10,416'; Attempting to pull 8 5/8" Casing
4-24-72 TD 10,416'; PLUGGED & ABANDONED
 LOG TOPS: Anhydrite 1810', Yates 3475', Cherry
 Canyon 6335', Brushy Canyon 7325', Bone Spring
 8105', First Bone Spring Sand 8747', Second
 Bone Spring Sand 9592'
4-29-72 COMPLETION REPORTED

COUNTY	LEA	FIELD	Lea	STATE	NM	30-025-24034
OPR	GULF OIL CORP.					MAP
	1 Lea "AP" State					
	Sec 30, T-19-S, R-35-E					CO-ORD
	2090' FSL, 760' FEL of Sec					
	Spd 2-13-72					
	Cmp 4-18-72					
		CLASS		EL		
	FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING						
13 3/8" at 358' w/450 sx						
8 5/8" at 4040' w/265 sx						
5 1/2" at 10,416' w/200 sx (Pulled)						
5 1/2" at 6516' w/600 sx						
LOGS EL GR RA IND HC A						
	ED 10,416'					
PLUGGED & ABANDONED						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	McVay	PROP DEPTH	10,400'	TYPE	RT
DATE					

P.R. 2-8-72; Opr's Elev. 3759' GL
FD 10,400' RT (Bone Spring)
Contractor - McVay

2-14-72 ED 860'; WOC
2-18-72 Drig. 3376' anhy
2-28-72 Drig. 6798' sd & lm
3-6-72 Drig. 9628' lm & sh
3-13-72 ED 10,416'; Prep smt 5 1/2" casing
3-20-72 ED 10,416'; PED 10,391'; Swbg
Perf 10,088-100' w/2 SPF
Acid (10,088-100') 1000 gals
Swbd 2 BEFA w/trace oil (10,088-100')
Acid (10,088-100') 3000 gals
Swbd 2 BO + 25 BW in 8 hrs