Submit 3 Copi to Appropri District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Ferm C-103 Revised 1-1-39

DISTRICT

P.O. Box 1980, Hotbs, NM 88240

P.O. Drawer DD, Artesia, NM \$8210

OIL CONSERVATION DIVISION WELL API NO. P.O. Box 2088 30-025-24094 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease STATE FEE 🗔 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. B1626 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: CAS WELL X STATE "V" OTHER 2. Name of Operator & Well No. AMERADA HESS CORPORATION 6 3. Address of Operator 9. Pool same or Wildon DRAWER D, MONUMENT, NEW MEXICO 88265 EUNICE-MONUMENT G/SA 4. Well Location H: 990' Feet From The EAST 1650 Feet From The NORTH __ Line and 36 198 Range LEA Section Township **NMPM** County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3604' DF Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 4/5 THRU 4/19/91 MIRU TYLER WELL SVC. PULLING UNIT & TOH W/RODS & PUMP. INSTALLED BOP & TOH W/TBG. TIH W/4-1/2" MD. R DBL. GRIP PKR. SET O.E. AT 3800' & SWABBED WELL. JOHN WEST ENGR. RAN TANDEM BOMBS. PULLED BOMBS & TOH W/PKR. TIH W/RBP & PKR., SET RBP AT 3810' & PKR. AT 3800'. TESTED RBP TO 2000#. HELD OK. TOH W/PKR. SCHUMBERGER RAN GR-CCL LOG FR. 3800'-3400'. PERF. EUNICE MONUMENT G/SA ZONE. 4-1/2" LINER FR. 3750'-3754' & FR. 3760'-3776' W/4 SPF, TOTAL 88 SHOTS USING 3-3/8" CSG. GUN. TIH W/MD. R DBL. GRIP PKR. SET AT 3711'. LOADED CSG. & TESTED TO 500# & TESTED TBG. TO 2500#. HELD OK. HALLIBURTON ACIDIZED G/SA ZONE PERFS. FR. 3750'-3776' W/1000 GALS. 18% NE-FE HCL ACID. SWABBED LOAD. JOHN WEST ENGR. RAN TANDEM BOMBS. PULLED BOMBS & RELEASED PKR. RE-SET RBP AT 3714' & PKR. AT 3704'. TESTED RBP TO 2000#. HELD OK. (OVER) SUPV. ADM. SVC. 4/26/91 SIGNATURE TYPE OR PRINT NAME R. L. WHEELER, JR. TELEPHONE NO. 393-2144 **Drig.** Signed by (This space for State Use) Paul Kautz

CONDITIONS OF AFFROYAL, IF ANY:

- Geologist

TOH W/PKR. SCHUMBERGER PERF. EUNICE MONUMENT G/SA ZONE 4-1/2" LINER FR. 3672'-3680' W/ 4 SPF, TOTAL 36 SHOTS USING 3-3/8" PERF. GUN. TIH W/PKR. SET AT 3620' & TESTED CSG. TO 500# & TBG. TO 3000#. HELD OK. SWABBED LOAD. JOHN WEST ENGR. RAN TANDEM BOMBS. PULLED BOMBS, RELEASED PKR. & LATCHED ONTO RBP. TOH W/PKR. & RBP. TIH W/BAKER AD-1 PKR. & 1-3/4" TBG. PUMP BARREL ON 2-3/8" & 2-7/8" TBG. SET PKR. AT 3798' & PUMP BARREL AT 3779'. REMOVED BOP & INSTALLED WELL HEAD. TIH W/1-3/4" X 4' PUMP PLUNGER ON RODS & RESUMED PUMPING WELL.

TEST OF 4/24/91: PUMPED 31 B.O., 34 B.W. & 42 MCFGPD IN 24 HRS. ON 64" X 8 SPM.

APR 3 e 1991

(42. - 48 (4. - 12