

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 037846 57683

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL ☒ GAS ☐  
WELL WELL OTHER

2. NAME OF OPERATOR

MorOilCo, Inc.

3. ADDRESS OF OPERATOR

P.O. Drawer 1 Artesia, NM 88211-0269

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL 660' FWL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gavilon Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 33 T20S R33E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3645.5 GR

12. COUNTY OR PARISH

Lea

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/25/87 Tied in 10-3/4" casing & prepare to drill out.

11/28/87 Commence drillins; drill top plug to 93'.

12/08/87 (1) Drill first plug to 93'.

(2) 2nd plug at 1208'.

(3) 3rd plug at 3115'.

(4) Tag top of 8-5/8" liner at 3871'.

(5) 4th plug at 4673'.

(6) 5th plug at 8792'.

Circulate hole with 2% KCl. Pressure casing to 1500# with no decline in pressure.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Frank A. Mays*

TITLE

*Vice Pres*

DATE

*12/10/87*

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAY 27 1988