

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 0378446
2. NAME OF OPERATOR Teal Petroleum Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Drawer 2358, Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 660' FWL		8. FARM OR LEASE NAME Aztec-Federal
14. PERMIT NO. Letter of 4-23-73		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3645.5GR 3656 KB		10. FIELD AND POOL, OR WILDCAT Salt Lake, So., Morrow
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T-20-S, R-33-E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data.

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Subject well is non-commercial from the Morrow formation. It is proposed to P & A well as follows:

1. Squeeze producing perforations below pkr. @ 13,346 w/50 sks. cement or B.P. w/20' cement on top.
2. Circulate hole (760 Bbls.) w/9.5# mud w/25 sks. gel/100 Bbls.
3. Spot cement plugs as follows:

Sacks	Depth
50	10,800-11,000
35	8,400-8,550
50	4,600-4,800
200	3,200-3,600
100	1,300-1,500
20	surface

4. Clean location to meet BLM requirements and place marker to meet NMOCC requirements.
5. Work will start around July 1, 1975 or on approval.

18. I hereby certify that the foregoing is true and correct

SIGNED

Douglas W. Rice

TITLE

District Engineer

DATE 6-10-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE