

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B 869	
7. Unit Agreement Name	
8. Farm or Lease Name	
State F	
9. Well No.	
6	
10. Field and Pool, or Wildcat	
Eunice-Monument G-SA	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator
Amerada Hess Corporation
3. Address of Operator
Drawer D, Monument, New Mexico 88265
4. Location of Well
UNIT LETTER M, 990 FEET FROM THE South LINE AND 610 FEET FROM THE West LINE, SECTION 36, TOWNSHIP 19S, RANGE 36E, NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3596' GL.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Leatherwood Drilling Company spudded 12½" hole at 10:00 A.M. 5-31-73. Finished 12½" hole to 1010' at 4:30 A.M. 6-2-73. Ran 32 jts. 9-5/8" O.D. 32.3 lb. casing set at 1010'. Cemented w/200 sks. of Class "C" low density cement, and 200 sks. of Class "C" cement w/2% calcium chloride. Cement circulated. WOC 18 hrs. tested casing w/1000 lbs. ½ hr. OK. Started drilling 8-3/4" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. E. Hargrave TITLE Drilling Supervisor DATE 6-6-73

APPROVED BY J. J. Ramey TITLE Dist. L. Secy. DATE 6-6-73

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 1 1971

CIL CONSERVATION COM.
HOLDS, N.Y.