

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate  
(Other instructions on  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 065658

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Box 806, Eunice, New Mexico 88231

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

990' FNL & 990' FWL

7. UNIT AGREEMENT NAME

Teas Yates Unit

8. FARM OR LEASE NAME

Tract No. 5

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Teas Yates

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

14-T20S-R33E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Dated 5-6-74

3570' GR

12. COUNTY OR PARISH

Lea

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒  
☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Rigged up well servicing unit.
2. Ran 435' 5½" OD 16.87# K-55 FJ liner with Baker Duplex Washdown Whirler Float Shoe on 2-3/8" OD EUE tubing. Pumped 50 sks Class "C" cement with 5# sand per sk. Could not release tubing from liner. Shut off tubing leaving 700' in hole.
3. Rig up reverse circulation. Fished out or drilled up 2-3/8" tubing to 3362'.
4. Ran Acoustic cement Bond Log.

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE

Area Supervisor

DATE

9-24-74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

\*See instructions on Reverse Side

