

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

5-NMOCC
1-File

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT 2-1 (FORM C-101) FOR SUCH PROPOSALS.)</small>		
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name	
2. Name of Operator GETTY OIL COMPANY	8. Form or Lease Name T. ANDERSON	
3. Address of Operator P.O. BOX 249, HOBBS, NEW MEXICO 88240	9. Well No. 4	
4. Location of Well UNIT LETTER I , 2223 FEET FROM THE SOUTH LINE AND 853 FEET FROM THE EAST LINE, SECTION 8 TOWNSHIP 20 RANGE 37 N.M.P.M.	10. Field and Pool, or Wildcat UNDESIGNATED	
15. Elevation (Show whether DF, RT, GR, etc.) 3546.1 GR	12. County LEA	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Capitan Drilling Company spudded at 2:00 A.M. 8-14-76. Drilled 17-1/2" hole to 318'. Set 13-3/8" 48# H-40 casing at 317'. Cemented with 320 sacks Class "C" with 2% Cacl and 1/4# Celloflakes per sack. Circulated an estimated 85 sacks cement. W.O.C. 24 hours. Tested 13-3/8" casing @ 1000# for 30 minutes with no drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY:

SIGNED **C. L. WADE:** **C. L. Wade** TITLE **AREA SUPERINTENDENT** DATE **8-20-76**

APPROVED BY: TITLE: DATE:

CONDITIONS OF APPROVAL, IF ANY:

WLG/bh

AUG 23 1976

RECEIVED

AUG 23 1976

OIL CONSERVATION COMAL
HOBBS, N. M.