

NO. OF COPIES RECEIVED		
DISTRIBUTION		
DATE FILED		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR INFORMATION TO THE PUBLIC OR TO THE PUBLIC OF THE STATE OF NEW MEXICO. IT IS A REPORT TO THE COMMISSION.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Cleary Petroleum Corporation

Address of Operator
P. O. Drawer 2358, Midland, Texas 79702

Location of Well
UNIT LETTER **P** **760** FEET FROM THE **South** LINE AND **660** FEET FROM
THE **East** LINE, SECTION **25** TOWNSHIP **20-S** RANGE **32-E** NEARBY

13. Elevation (Show whether DF, RT, GR, etc.)
3588' GR

5a. Indicate Type of Lease
State ☐ Fee ☒*

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name
Felmont Federal

9. Well No.
1

10. Field and Pool, or Wildcat
Undesignated

12. County
Lea

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
REPAIR OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	Plug Back ☒

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1403.

- 3-9-78 TIH to Csg Shoe @ 5196' taking SLM. Did not find any trace of cmt plug that was spotted from 6500' to 5900'. Tagged cmt plug @ 6833'. TIH w/DP open-ended to spot cmt plug from 6500' to 5900'.
- 3-10-78 Finished TIH w/DP open-ended to 6500'. Circ hole. RU Howco. Spotted 215 sx Class "C" containing 10 lbs per sk Sand & mixed @ 15.0 PPG from 6500' up. TIH & tagged top of cmt plug @ 6022' after 30 hrs WOC.
- 3-11-78 Washed & circ'd contaminated cmt from 6022' to 6200'. POH. TIH w/DP open-ended to 6200'. Spotted 175 sx Class "C" cmt containing 10 lbs/sk Sand & 0.3% CFR-2 mixed @ 15.0 PPG from 6200' up. POH.
- 3-12-78 Tagged top of cmt plug @ 5900'.
- 3-13-78 Circ & WOC for 48 hrs. Drld cmt plug from 5900' to 6070'. Tested cmt plug w/40 M lbs weight & 1900 PSIG PP for 15". No washout. PBTD 6070'.
- 3-14-78 TIH w/Dyna-drill BHA & checked operation OK. Set Dyna-drill @ N 5° E & started Directional Drilling Operations. (con't on additional pg)

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Buddy J. Knight TITLE District Production Mgr. DATE 4-11-78

ORIG. SIGNED BY Les Clements TITLE _____ DATE APR 14 1978

REMOVED BY _____

CONDITIONS OF APPROVAL, IF ANY Oil & Gas Insp.

RECEIVED

APR 20 1978

OIL CO. IS L...-M COMM,
HOBBS, N. M.