| Form 9-331 (May 1963) | UNITED STATES DEPARTME: OF THE INTERIOR GEOLOGICAL SURVEY | 5. LEASE DESIGNATION AND SERIAL NO. |
|---|---|---|
| (Dø not u | SUNDRY NOTICES AND REPORTS ON WELLS use this form for proposals to drill or to deepen or plug back to a different res Use "APPLICATION FOR PERMIT_" for such proposals.) | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| | GAS WELL X OTHER | 7. UNIT AGREEMENT NAME |
| 2. NAME OF OPER | ATOR | 8. FARM OR LEASE NAME |
| Cleary Pe 3. Address of of | troleum Corporation | 9. WELL NO. |
| P. O. Dra 4. LOCATION OF W See also space At surface | Wer 2358, Midland, Tx. 79702 VELL (Report location clearly and in accordance with any State requirements.* 17 below.) | 10. FIELD AND POOL, OR WILDCAT Undesignated |
| | & 660' FEL e location: 1320' FNL & 1320' FEL | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA |
| 14. PERMIT NO. | 15. ELEVATIONS (Show whether DF, RT, GR, etc.) | Sec. 25, T-20-S, R-32-E 12. COUNTY OB PARISH 13. STATE |
| Letter da | ted 12-28-77 3588' GR | Lea N. M. |
| 16. | Check Appropriate Box To Indicate Nature of Notice, R | |
| | NOTICE OF INTENTION TO: | SUBSEQUENT REPORT OF : |
| TEST WATER S FRACTURE TRE SHOOT OR ACH REPAIR WELL (Other) 17. DESCRIBE PROPE proposed wo nent to this y | BAT MULTIPLE COMPLETE FRACTURE TEEA DIZE ABANDON* SHOOTING OR A CHANGE PLANS (Other) (Note : R COSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give per ork. If well is directionally drilled, give subsurface locations and measured a | FF REPAIRING WELL ALTERING CASING CIDIZING ABANDONMENT* CIDIZING Back Ceport results of multiple completion on Well no or Recompletion Report and Log form.) |
| 2-28 - 78 | Dev surv 29 3/40 @ 7270', N 41 ⁰ W; 29 3/40 | @ 7355', N 41 ⁰ W. |
| 3-4-78 | Dev surv 27 3/4 ⁰ @ 7487', N 40 ⁰ W. | |
| 3-6-78 | Dev surv 26 3/4 ⁰ @ 7611'. N 41 ⁰ W. | |
| 3-7-78 | Drld to 7777'. Ran Eastman Survey. Dev sur Drld to 7798'. POH w/Bit. Cut drld line. to 6500'. Caliper Surv indicated 10" to 15' Notified Arthur Brown w/USGS about Plugback Spotted 240 sx Class "H" cmt containing 0.5% lbs/sk sand from 6510' to 5900'. Used 70 bb bbls Diesel behind cmt job. Plug down @ 4:0 | Ran Caliper Surv from 5196' 'washouts from 5200' to 6200'. CMT job. TIH w/DP to 6500'. & CFR-2, 5 lbs/sk salt, & 5 ols Diesel Spacer ahead & 20 |
| 3-8-78 | POH w/STDS DP. PD 5900' PBTD. Circ cmt. T | TOH. SI well to WOC. RECEVED FEB 13 1978 |
| | | |
| 18. I hereby certify | y that the correct and correct | U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO tion Mgr. DATE 3-10-78 |
| (This space for | Ederal or State office use) | |
| APPROVED BY | | |
| | OF APPROVAL, IF ANY: *See Instructions on Reverse Side | ACCEPTED FOR RECORD |
| | | U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO |

¥

RECENCED

MAR 1 4 1978

OIL CONSERVATION COMM. HOBBS, N. M.