Form 9-331 Dec. 1973

HNITED STATES

Form A	pproved	I.		
Budget	Вигели	Nο	42_R1	42

DEPARTMENT OF THE INTERIOR	5. LEASE b			
GEOLOGICAL SURVEY	LC-031736-a			
GLOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)				
	8. FARM OR LEASE NAME			
1. oil gas other	Gillully A Federal			
2. NAME OF OPERATOR	9. WELL NO.			
Amoco Production Company	16 10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR	Eunice-Monument (Grayburg)			
P.O. Drawer "A", Levelland, Texas 79336	11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA			
AT SURFACE: 840' FNL X 2080'FEL, Sec 24 (Unit B AT TOP PROD. INTERVAL:	24-20-30			
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: NW14, NE14)	Lea NM			
	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				
·	3536.6 GR (SHOW DF, KDB, AND WD)			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3350.0 dK (a g			
FRACTURE TREAT				
SHOOT OR ACIDIZE				
REPAIR WELL PULL OR ALTER CASING	(Next Report results of multiple completion			
MULTIPLE COMPLETE JAN 9 1	(Next Euleport results of multiple completion or zone change on Form 9–330.)			
CHANGE ZOIVES	YYY Y GULDE D GERT SI			
Casing & Cas	L SURVEY			
TOBBS, NEW	MEXION D. BERN R. E. E. G. G. C.			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dire measured and true vertical depths for all markers and zones pertinent.	all pertinent details, and give pertinent dates,			
measured and true vertical depths for all markers and zones pertinent	to this work.)*			
Drilled to TD 4102' and ran 5 1/2" 14# J-55 ar Cemented with 581 sx Class C Plus additives				
Cemented with 581 sx Class C Plus additives. 12/24/78. Released rig 10:00 a m 12/24/79	Circulated 116 cv pp 4.20			
12/24/78. Released rig 10:00 a.m. 12/24/78. plug 4056'-4090'. Test casing 1500# for 30 mi	WOC 6 days. Drilled out coment			
plug 4056'-4090'. Test casing 1500# for 30 mi	inutes. Test O.K.			
	() () () () () () () () () ()			
	역사 위 등합 - 현 - 기 시설 및 설명 관계합 - 및 국 - 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기			
•				
subsurface Safety Valve: Manu. and Type				
	Set @ Ft.			
8. I hereby certify that the foregoing is true and correct				
IGNED TITLE Admin. Supervisi	or January 5, 1979			
(This space for Federal of State County RECORD)				
PPROVED BY	DATE			
THOUGHT IF ANY:	The state of the s			
1-Houston JA	N SURVEYED TE			
1-Houston 1-SUSP 1-DE *See Instructions on Reverse State	LOGICA MEXICO			
1-DE • See Instructions on Revealed Side	6, NEV			

WINDOW WATER TO THE TOTAL TO

OIL SE TOUR ME