

N. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CEMENT OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT "A" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
		5. State Oil & Gas Lease No.
6. Name of Operator Amoco Production Company		7. Unit Agreement Name
8. Address of Operator P.O. Drawer "A", Levelland, Texas 79336		8. Farm or Lease Name South Hobbs (GSA) Unit
9. Location of Well UNIT LETTER <u>E</u> <u>1450</u> FEET FROM THE <u>North</u> LINE AND <u>150</u> FEET FROM <u>West</u> <u>4</u> TOWNSHIP <u>19-S</u> RANGE <u>38-E</u> N.M.P.M.		9. Well No. 121
		10. Pool and Pool, or Wildcat Hobbs Grayburg San Andres
11. Elevation (Show whether DF, RT, GR, etc.) 3613.9 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 11-11-78, Cactus (rig #63) spudded a 15" hole at 6:00 p.m. Drilled to TD 1431' and ran 11 3/4" 42# H-40 ST & C casing set at 1431'. Cemented with 750 sx Class "C" cement plus additives and 100 sx Class "C" cement plus 2% CACL. Circulated 150 sx. PD 6:30p.m. 11-14-78. WOC 18 hours. Test casing with 1000# for 30 minutes. Test OK. Reduced hole to 11" and resumed drilling.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Assist. Admin. Analyst DATE 11-22-78

APPROVED BY Jerry Sexton TITLE Dist. I, Supv. DATE NOV 29 1978

CONDITIONS OF APPROVAL, IF ANY:
O & 4 NMOCC-H 1-Susp 1-Div 1-DE