

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>
1. Name of Operator Amoco Production Company		
2. Address of Operator P. O. Box 68, Hobbs, NM 88240		
3. Location of Well UNIT LETTER <u>H</u> <u>2390</u> FEET FROM THE <u>North</u> LINE AND <u>150</u> FEET FROM THE <u>East</u> LINE, SECTION <u>6</u> TOWNSHIP <u>19-S</u> RANGE <u>38-E</u> NMPM.		

7. Unit Agreement Name
8. Farm or Lease Name South Hobbs (GSA) Unit
9. Well No. 123
10. Field and Pool, or Wildcat Hobbs Grbg. San Andres
11. Elevation (Show whether DF, RT, GR, etc.) 3619.9 GR
12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Run 5-1/2" Liner</u> <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Request permission to run a 5-1/2" 14# K-55 ST&C liner set at 4286'. Top of liner 3706'. Will cement with 125 sx Class C cement with 5# salt/sx. Will perforate 4176'-4250' with 2 JSPF. Acidize with 350 gal 15% NE-HCL acid. Install pump equipment and pump test.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Assist. Admin. Analyst DATE 12-26-79

APPROVED BY [Signature] TITLE [Signature] DATE DEC 28 1979

CONDITIONS OF APPROVAL, IF ANY:

0+4 NMOC-D-H, 1-Hou, 1-Susp, 1-BD, 1-Petro Lewis, 1-Shell, 1-Sun