

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER-	7. Unit Agreement Name
2. Name of Operator SUN OIL COMPANY	8. Farm or Lease Name Maveety-State Gas Com.
3. Address of Operator P.O. BOX 1861, MIDLAND, TX 79702	9. Well No. 8
4. Location of Well UNIT LETTER 0 810 FEET FROM THE South LINE A- 2030 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 19-S RANGE 36-E NMPM.	10. Field and Pool, or Wildcat Eumont Gas
11. Elevation (Show whether DF, RT, GR, etc.) 3596' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPERATIONS ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER foam frac & acdz ☒	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- KILL WELL W/MINIMUM VOLUME OF 5% KCL.
- MIRU, INSTALL BOP & TALLY OUT TBG.
- RIH W/PERMALATCH PKR, OSTSD W/TYPE "N" LANDING NIPPLE (1.791" ID), X-OVER SUB ON 2-7/8" WS.
- SPOT 232 gal of 15% NEFEHCL FROM 3576 to 3350, PU TO 3300', CIRC 5 BBL 5% KCL DOWN BACKSIDE & SET PKR @ 3300'.
- FRAC PFS 338013576 IN 3 STAGES W/49,800 GAL 70 QUALITY FOAM & 46,200# 20/40 SD.
- WELL SHOULD CLEAN UP-BUT SWAB IF NECESSARY
- SET PLUG ON WL IN "N" PROFILE, UNLATCH FROM SEAL ASSEMBLY & POH W/WS & OSTSD.
- RIH W/OS ON 2-3/8" PROD STRING TO 30' ABOVE PKR CIRC & LOAD BACKSIDE W/PKR FLUID TRETO KW-79.
- LATCH ON TO SEAL ASSEMBLY W/OS, RETRIEVE PLUG ON WL, PRODUCE TEST WELL.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Leresa Bradley</u>	TITLE <u>Accounting Asst. II</u>	DATE <u>3-13-81</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist. L. Supv.</u>	DATE <u>MAR 16 1981</u>
CONDITIONS OF APPROVAL, IF ANY:		