

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(On reverse side of form, instructions for completion of this report are given.)

1. oil well ☐ gas well ☐ other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P.O. Drawer "A", Levelland, Texas 79336
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE 1980' FILL & 1650' FEL. Sec 27
AT TOP PROD. INTERVAL: (Unit G, SWL, NEU)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON ☐

SUBSEQUENT REPORT OF:

(other) gas kick; change casing size

5. WELL
105-10601
6. INDIAN, ALIEN, OR TRUST NAME
7. UNIT AGREEMENT NAME
8. FARM OR RANCH NAME
Federal Y Co.
9. WELL NO.
1
10. FIELD OR WELDCAT NAME
WC Morrow
11. SEC., T., R., M., OR BLK. AND SHADY OR AREA
27-20-28 33
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3623.2 GR

RECEIVED

APR 12 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled to a TD of 13,065' and evidenced gas kick. Shut down drilling operations at 10:30 PM 4/6/79, and circulated gas out. Raised mud weight to 11#. Will increase mud weight until gas flow is killed.

Propose to run 7" 26#-32# casing to a TD of 13,065', and tie back cement to the 9 5/8" casing already set at 5629'. After 7" casing is set, will drill to a TD of 14,500 and then set 5" liner. Gas kick reported to Jim Sims, USGS by Ray Cox 4/9/79. Gas kick also reported to Jerry Sexton, IMOC.

Subsurface Safety Valve: Make, and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Admin. Supervisor

DATE

April 11, 1979

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

0-4-USGS, H

1-Houston

1-Susp

1-DWC

1-Supron

1-Arco

1-Grace Petro (See Instructions on Reverse Side)

