

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
Estoril Producing Corporation
3. ADDRESS OF OPERATOR  
11th Floor Vaughn Bldg., Midland, Tx. 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980 FSL & 1980 FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE

LC-064-194

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Union Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Lea Brushy Canyon

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9, T20S, R34E

12. COUNTY OR PARISH 13. STATE

Lea

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3636.5 GL

(NCTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)\*

1. Set 5½" CIBP @ 7250', capped w/35' cement (tagged)
2. Loaded hole w/mud laden fluid
3. Cut off 5½" csg @ 4700' and pulled
4. Spotted 50 sx cement from 4770-4622' thru tbq (tagged)
5. Spotted 100 sx (300') cmt from 3450-3150' inside 9-5/8"
6. Spotted 100 sx (300') cmt from 1600-1300' inside 9-5/8"
7. Spotted 25 sx (50') from 50' to surface
8. All plugs placed thru tbq w/mud laden fluid between plugs
9. 8900' 5½" csg left in hole @ 13,600'; 5215' 9-5/8" csg left @ 5215'; 853' 13-3/8" csg @ 853'
10. Set Dry Hole marker. Plugging completed 6-29-84.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Cliff Duescher TITLE Engineer Mgr. DATE 7-9-84

(This space for Federal or State office use)

APPROVED BY Mark H. Hulse TITLE Chief of Party DATE 5-6-84  
CONDITIONS OF APPROVAL, IF ANY: