

COPY TO O. C. C.

~~PREVIOUSLY SUBMITTED JULY 9, 1979. RE-SUBMITTED TO REVISED FORM.~~

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Estoril Producing Corporation
3. ADDRESS OF OPERATOR
1120 Vaughn Building, Midland, TX 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1980' FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) Casing information on new well

5. LEASE
LC-064194
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Union Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 9, T-20-S, R-34-E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3636.5 GR

RECEIVED
JUL 11 1979
(NOTE: Report results of multiple completion or zone change on Form 9-330.)
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-11-79

Depth 5215'. Ran 50 jts (2186.10') of 9 5/8", OD, 36#, S-80 ST&C casing, 71 jts (2810.40') 9 5/8", 36# K-55, ST&C casing, 5 jts (208.75') of 9 5/8", 40#, S-95, ST&C casing, floats & sleeve 7.0'. Total of 126 jts (5212.95') set at 5215', stage sleeve at 3570'. Cemented with 200 sacks EJ lite + 2% CCL, 8# salt, 5# D-7, 1/4# CF per sack, 200 sacks Class C + 2% CCL. Plug down at 4:00 PM on 4-11-79. Top of cement: 4200'. Opened sleeve at 3570', cemented with 900 sacks BJ lite + 2% CCL from 3570' to 4200' by Temperature Survey. Closed sleeve, reversed out, re-opened sleeve. Cemented with 900 sacks BJ lite + 2% CCL, no returns. Closed sleeve, rev. out. Press. tested csg & BOP to 2000#, held OK. Pulled out of hole, close blind rams, press to 1000#, Set @ 1000# Ft.

18. I hereby certify that the foregoing is true and correct

PLEASE SEE ATTACHED SHEET

SIGNED Carolyn Hickman TITLE Agent

DATE July 10, 1979

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
JUL 12 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

ATTACHMENT TO FORM 9-331 -
Union Federal #1 well
Lea County, New Mexico

4-11-79 - continued

on 9 5/8" casing, cemented through bradenhead with 1600 sacks BJ lite +
2% CCL + 8# salt, 5# D-7, 1/4# CF per sack to 3570' by Temperature Survey.
Job complete at 7:00 AM on 4-13-79.

RECEIVED

JUL 17 1979

O.C.D. HOBBS, OFFICE