

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	TRUE VERTICAL DEPTH FEET	VERTICAL SECTION FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DUG LEG SEVERITY DEG/100FT
0.	0 0	0	0.00	0.00	0.00	0.0
100.	0 30	S 44 E	100.00	-0.35	0.31 S	0.5
200.	0 15	S 2 E	200.00	-0.70	0.90 S	0.4
300.	0 0	0	300.00	-0.74	1.12 S	0.2
400.	0 30	S 50 E	399.99	-1.12	1.40 S	0.5
500.	1 15	S 29 E	499.98	-2.27	2.57 S	0.8
600.	1 30	S 25 E	599.95	-3.71	4.71 S	0.3
700.	1 15	S 23 E	699.92	-5.05	6.90 S	0.3
800.	1 15	S 28 E	799.90	-6.31	8.87 S	0.1
900.	1 15	S 32 E	899.88	-7.71	10.76 S	0.1
1000.	1 15	S 29 E	999.85	-9.12	12.64 S	0.1
1100.	1 15	S 18 E	1099.83	-10.32	14.63 S	0.2
1200.	1 15	S 13 E	1199.80	-11.26	16.74 S	0.1
1300.	1 0	S 24 E	1299.79	-12.19	18.59 S	0.3
1400.	0 45	S 49 E	1399.77	-13.28	19.81 S	0.5
1500.	0 30	S 78 E	1499.77	-14.32	20.29 S	0.4
1600.	0 45	S 66 E	1599.76	-15.39	20.63 S	0.3
1700.	0 45	S 68 E	1699.75	-16.67	21.14 S	0.0
1800.	0 30	S 85 E	1799.75	-17.75	21.39 S	0.3
1900.	0 15	S 37 E	1899.74	-18.35	21.70 S	0.4
2000.	0 15	N 77 E	1999.74	-18.76	21.84 S	0.3
2100.	0 30	N 49 E	2099.74	-19.28	21.55 S	0.3
2200.	0 30	N 51 E	2199.74	-19.84	20.99 S	0.0
2300.	1 0	N 72 E	2299.73	-20.86	20.36 S	0.6
2400.	0 45	N 80 E	2399.71	-22.26	20.00 S	0.3
2500.	0 45	N 72 E	2499.71	-23.45	19.68 S	0.1
2600.	0 45	N 68 E	2599.70	-24.59	19.23 S	0.1
2700.	1 0	N 57 E	2699.68	-25.80	18.53 S	0.3
2800.	1 0	N 48 E	2799.67	-26.98	17.47 S	0.2
2900.	1 0	N 54 E	2899.65	-28.13	16.37 S	0.1