

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>1586'</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt <u>2380' 1700'</u>	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt <u>3440' 2480'</u>	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>2105'</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers <u>2930'</u>	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4400'</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Elinebry <u>5489'</u>	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>6824'</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard <u>7058'</u>	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
2500	2750	250	Anhydrite & salt				
2750	3750	1000	Anhydrite				
3750	4250	500	Anhydrite & dolomite				
4250	6920	670	Dolomite				
6920	7070	150	Limestone				
7070	7200	130	Dolomite				
7200	7400	200	Limestone				
7400	7500	100	Dolomite				
7500	7700	200	Limestone				
7700	TD	100	Dolomite				

RECEIVED JUL - 6 1979
O.C.D. HOBBS, OFFICE

RECEIVED JUL - 6 1979
O.C.D. HOBBS, OFFICE