Form Approved. Budget Bureau No. 42-R1424

UNI.LD STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM_10787
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	Nadine Federal
well well other	9. WELL NO. 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
2. NAME OF OPERATOR	1 5.8 d 9 8 9 5 5
North American Royalties, Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Nadine Drinkard
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 23, T-19-S, R-38-E
below.) AT SURFACE:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: 660/N+W	Lea = New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	1 Third 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	GR 3602 - KB 3613.5
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	C I W C C
FRACTURE TREAT	
DEPAIR WELL	(NOTE: Parity results of multiple completion or zone
PULL OR ALTER CASING APR	2 1 1980 change on Form 9–330.)
MULTIPLE COMPLETE []	그 그 그 그 그 그 이 그 사람들은 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
CHANGE ZONES U. S. GEOLO ABANDON* U. S. GEOLO HORRS	OGICAL SURVEY
(other) Potential Well	NEW MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d	e all pertinent details, and give pertinent dates, lirectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertiner	nt to this work.)*
	77451 40 70001
TD 7950', PBTD 7720'; Perforated with	12 Shots from //o5 to /oso
and acidized with 1800 gallons of 15% bearing and a CIBP was set at 7740' an	d 201 coment dummed on top
Perforated from 7657'-7669' (8 holes)	and acidized with 2200 gals
15% HCL. Perforated from 7580'-7650 1	/2! (14 holes) and acidized
with 1500 gals. 15% HCL. Ran 2 3/8" t	h_0 to 7649 and 3/4" and 7/8"
rods and 2" X 1 1/2" X 16' bottom hole	nump to 7613' Installed
pumping unit and electricity. Will po	tential well on 4-23-80.
pumping unit and electricity. Will po	
	August San
Sel Carrection	
Il avulland	

(This space for Federal or State office use)

Subsurface Safety Valve: Manu. and Type _

DATE

U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO