

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-3558 & L-3678	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Kelloil, Inc.		STATE 30 COM
3. Address of Operator		9. Well No.
900 Neil P. Anderson Bldg., 411 W. Seventh, Ft. Worth, TX 76102		1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>G</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM		WILDCAT
THE <u>East</u> LINE, SECTION <u>30</u> TOWNSHIP <u>20-S</u> RANGE <u>35-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3714.7 GL; 3736.7' KB		LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER <u>Completion Operations &amp; Abandonment</u> <input checked="" type="checkbox"/>	
		of zones tested	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Perforated Brushy Canyon Sand from 8390'-8422' with two holes per foot on 3-25-80. Acidized with 2000 gallons 15% HCL acid. Swab tested with no shows. Set Cast-Iron Bridge Plug @ 8300' with wireline and 35' of cement dumped on top of BP from 8265'-8300' on 3-27-80. Cut 4-1/2" casing @ 5850' and pulled out of hole on 3-28 and 3-29-80. Ran 2-3/8" tubing to 5957' and set cement plug for top of 4-1/2" casing and bottom of 9-5/8" intermediate casing (5440') with 300 sacks class C cement from 5957'-5280' on 3-29-80. Pulled tubing to 4300' and set 204' cement plug in 9-5/8" casing with 75 sacks class C from 4300'-4096' on 3-30-80. 8500' of 4-1/2" casing left in hole from 5850'-14,350'. 5440' of 9-5/8" casing in hole, cemented to surface. 865' of 13-3/8" casing in hole. To perforate Yates.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Harold E. Bunker TITLE Agent DATE 4-17-80