NO. OF COPIES REI							ب	30-02	15-26=	532
DISTRIBUTION NEW MEXICO OIL CONSERVATION COMMISSION										
SANTA FE					DWWI22L		Form C-101 Revised 1-1-5	5		
FILE							ſ	5A. Indicate	Type of Leas	
								STATE		
U.S.G.S.									& Gas Lease	المسسا
LAND OFFICE									a das Ecase :	
OPERATOR								,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	innin in the second sec
									1111111	
	PLICATION	FOR PE	RMIT TO DRILL,	DEEPEN	, OR PLUG E	BACK		<i>illilli</i>	111111	711111
la. Type of Work								7. Unit Agre	ement Name	
	DRILL X		DEEPEN			PLU	З ВАСК			
b. Type of Well				L				B. Farm or L	ease Name	
OIL WELL	GAS WELL X	OTHE	R		SINGLE X	м	ZONE	State "	L" Gas Co	omm.
2. Name of Operator								9. Well No.		
Amorada	Hess Cor	oration	n					3		
Amerada Hess Corporation								10. Field and Pool, or Wildcat		
Drawer D, Monument, New Mexico 88265								Eumont - Queen (gas)		
4. Location of Well			LOCATED 19	980	FEET FROM THE	Nort	hLINE		(XXX)).	//////
									///////////////////////////////////////	
AND 960	FEET FROM TH	West	LINE OF SEC.	20	TWP. 19-S	RGE. 3	7-Е ммрм		///////	
	<u>IIIIII</u>	IIIII		IIIII		()))		12. County		
())))))))))))))))))))))))))))))))))))))						/////		Lea		
	MMM	IIIII		$\Pi\Pi\Pi$		/////			111111.	//////
		///////		//////		/////		///////		
MMMMM	HHHHH	tttttt	tittittittitti		19. Proposed D	epth	19A. Formation		20. Rotary or	C.T.
				//////	3600		Queen		Rotarv	
21. Elevations (Shor	w whether DF, R	T, etc.)	21A. Kind & Status P	lug. Bond	21B. Drilling C	ontractor		22. Approx	. Date Work w	ill start
3653' GL.	3653' GL, 3663' DF Blanket Cattus Drlg. (1g. C	ο.	Novemb	er 15, 19	979
23.										
PROPOSED CASING AND CEMENT PROGRAM										

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12-1/4"	8-5/8"	24#	300 '	300 sks.	circ.
7-7/8"	5-1/2"	15.5#	3300 '	1200 sks.	circ.

Plan to drill a 12-1/4" hole to 300', set and cement 8-5/8" csg. at 300' w/300 sks. cement. WOC approx. 18 hrs. Drill 7-7/8" hole out fr. under 8-5/8" csg. to approx. 3300' or top of Queen and set 5-1/2" csg. at 3300' & dement w/approx. 1200 sks. cement. Drill out fr. under 5-1/2" using gas and complete as a Eumont Yates Seven Rivers Queen gas well.

Blow out equipment consists of 10" Cameron Type F Series 900 dbl. hydril w/Payne closing unit. Gas separator and de-gasser complete w/automatic choke. All BOP equipment will be checked periodically by a drilling company driller and Amerada Hess well site drilling supervisor.

> ZENER VED FOR CO DAYS UNLESS (DRILLING COMMENCED,

EXPIRES

- 75

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUC-TIVE ZONE, GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signe W.A. Merrick Tille Dist	Date 11-2-79		
(This space for State Use) APPROVED BY OM W. UMMMANTITLE	Geologia	NUV 5 1979	
CONDITIONS OF APPROVAL, IF ANY	•		

Before production from this well will be authorized, approval must be obtained for the non-standard proration unit.