

COPY TO O. C. C.
UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC 055715

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bordages

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Eunice Monument

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit Letter C

Sec. 33, T-19-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Great Western Drilling Company

3. ADDRESS OF OPERATOR

Post Office Box 1659 Midland, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

760' FWL, 1780' FWL, Sec. 33, T-19-S, R-37-E

Unit Letter C

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3584.6 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

01-19-80: TD @ 3950' 11:30 AM, 01-19-80. Ran 95 jts, 4 1/2" 10.5#/ft, J-55, ST&C CASING. Set 3,941.33' @ 3950.33' KBM. Cemented as follows: 500 gals. mud flush, followed with 600 sx Class "C" mixed at 14.8#/gal. Bumped plug with 1,500 psi, held. Job completed at 1:15 AM, 01-20-80. Used the following accessories: two cement baskets, 11 centrillizers, 28 cable wipers, Baker guide shoe and differential fill float collar. U. S. G. S. notified, did not witness.

01-20-80: Ran temperature survey, top of cement inside @ 3,875', top of cement outside at 2,210'.

Now waiting on completion unit.

RECEIVED

JAN 25 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

M. B. Myers

M. B. Myers

TITLE

Assistant General Superintendent

01-24-80


(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE



*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

8-47 - 485

RECEIVED

JAN 29 1980

OIL CONSERVATION DIV.