

vicinity of Pleistocene-aged lake beds.

Recommendations

NMAS recommends clearance for Great Western Drilling Company's proposed Bordages Well No. 4 and its access road and suggests that work-related activities proceed in accordance with company plans.

CONTR Cactus OPRSLEV 3584' GL, 3593' KB PD 3950' RT

F.R. 1-14-80
(Grayburg-San Andres)
1-15-80 Drlg 2750'
1-22-80 TD 3950'; WOCT
1-29-80 TD 3950'; RU pulling unit
2-5-80 TD 3950'; SD
Perf (Grayburg-San Andres)@ 3742', 3744', 3746',
3766', 3768', 3772', 3774-84', 3790-92', 3794-
3826', 3834-57', 3871', 3877', 3883' w/77 shots
(overall)
Acid (3742-3883') 20,000 gals (15%)
Frac (3742-3883') 14,000 gals + 20,000# sd
Swbd 39 BLW w/SSG in 8 hrs (3742-3883')
2-26-80 TD 3950'; Ppg Ld
3-3-80 TD 3950'; SD pmp repairs
3-11-80 TD 3950'; Sl
3-18-80 TD 3950'; Prep POT
Ppd 25 BF (25% oil) in 24 hrs (3742-3883')
5-4-8 NM

LEA
GREAT WESTERN
DRILLING CO.

Eunice-Monument
4 Bordages
Sec 33, T19S, R37E

NM
Page 2

5-19-80 TD 3950'; Complete
LOC TOPS: Yates 2625', Seven Rivers
2970', Penrose 3553', Grayburg-San
Andres 3716'
LOGS RUN: CNL, PDC
Rig Released 1-20-80
5-24-80 COMPLETION ISSUED

5-4-8 NM
LC 30-025-70009-80