

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR  
Amoco Production Company3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FNL & 1980' FWL, Sec. 14  
AT SURFACE: (Unit F, SE/4 NW/4)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

MAY 9 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

NM-16835

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal AG Com

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat West Osudo Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

14-20-35

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3695.2 RDB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to a TD of 13045' and DST #1 12960'-13031'. Resumed drilling and drilled to a TD of 13450'. Ran 4-1/2" liner set at 13448'. Cemented with 400 SX Class H cement with additives. WOC 19-1/2 hours. Top of liner at 11120'. Drilled cement in 7-5/8" casing. Will test casing when move in completion unit.

DST Attached

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bob Davis TITLE Admin. Analyst DATE 5-6-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-H 1-Hou 1-Susp 1-BD 1-Superior

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 20 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO