

10. Blowout Preventer Program is attached.
11. Type and characteristics of the proposed circulating medium or mediums to be employed for rotary drilling, and the quantities and types of mud and weighting material to be maintained.
 - 0 - 400' Native mud and fresh water
 - 400' - 5800' Native mud and brine.
 - 5800' - TD Commercial mud and brine with KCL for 6% system. Prior to Morrow penetration raise viscosity to 36-40 and reduce water loss to 6 cc
12. Testing, logging and coring programs to be followed with provisions made for required flexibility.
 - Comp Neutron Form Density
 - Dual Laterolog - Micro SFL
13. Any anticipated abnormal pressure or temperatures expected to be encountered or potential hazards, such as hydrogen sulfide gas, along with plans for mitigating such hazards.
 - None anticipated
14. Anticipated starting date and duration of operation.
 - 11-20-79 1-20-80
15. Other facets of the proposed operation operator wishes to point out for the Geological Survey's consideration of the application.

Request exemptions from the painting stipulations of Sec. 102 (a) (8) of the "Federal Land Policy and Management Act of 1976" to paint any tanks, separators, and treaters required for the production of this well, Amoco's standard gray color. If a pumping unit is required for the continued production of this well, it will be painted black with orange safety color coding which conforms with your current painting guidelines.