

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FEL, Sec. 14-T20S-R32E

5. Lease Designation and Serial No.

NM 63016

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Belco AIA Federal #1

9. API Well No.

30-025-26826

10. Field and Pool, or Exploratory Area

Und. Bone Springs/Delaware

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Perforate, Treat
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-7-91. Moved on. Loaded tubing. Installed BOP. Unset packer. WIH. Latched onto RBP w/ball catcher. POH. Perforated Bone Springs 9171-9201' as follows: 9171, 75, 79, 82, 86, 90, 96 and 9201' (8 holes-1 SPF); perforated Delaware sands 7313-7500' as follows: 7313, 28, 30, 32, 45, 47, 51, 59, 62, 68, 73, 77 and 7380' (13 holes-2 SPF), 7486, 89, 94, 96 and 7500' (10 holes-2 SPF). WIH w/RBP and packer. Set RBP 7750' and tested to 1500 psi. Set packer at 7250'. Acidized w/1500 gals 7 1/2% NEFE HLC acid. Ran pump and rods 3-23-91. RBP's @ 11000' and 7750' with retainer at 7650 w/10' cement cap. Perforations open: 7313-80' and 7486-7500'.

APPROVED FOR FILING
Adm

APR 26 1991

14. I hereby certify that the foregoing is true and correct

Signature [Signature]

Title Production Supervisor

Date 4-11-91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

RECEIVED

APR 30 1991

HOME OFFICE