

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-85

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator		Monument Abo Unit	
3. Address of Operator		8. Farm or Lease Name	
Amerada Hess Corporation		Monument Abo Unit	
4. Location of Well		9. Well No.	
Drawer "D", Monument, New Mexico 88265		1	
UNIT LETTER C 800 FEET FROM THE North LINE AND 1750 FEET FROM		10. Field and Pool, or Wildcat	
THE West LINE, SECTION 2 TOWNSHIP 20S RANGE 36E NMPM.		Monument Abo	
15. Elevation (Show whether DF, RT, CR, etc.)		12. County	
3598'GL 3613'RKB		Lea	

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Set surface casing.

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-28-80 - Spudded 17-1/2" hole @ 9:00AM. 10-28-80 - Drld. 17-1/2" hole to 470'.  
Ran 12 jts. 13-3/8" csg. set @ 470' & cemented w/500 sks. Class C cement w/additives.  
Cement circ. WOC & drld. cement fr. 381' to 450' & tested w/1000# press. f/30 min..  
Held OK. Drld. out cement to 470' & started drlg. 12-1/4" hole at 470'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. B. Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>2-17-81</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist. L. Supv.</u>	DATE <u>2-17-81</u>
CONDITIONS OF APPROVAL, IF ANY:		