

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
18634	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation		8. Farm or Lease Name Graham State (NCT-C) Com
3. Address of Operator P. O. Box 670, Hobbs, NM 88240		9. Well No. 9
4. Location of Well UNIT LETTER <u>B</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>25</u> TOWNSHIP <u>19S</u> RANGE <u>36E</u> NMPM.		10. Field and Pool, or Wildcat Eumont Gas
15. Elevation (Show whether DF, RT, GR, etc.) 3663' GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Perf, Acz, Frac

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Perf 3708-10', 3650-52', 3636-38', 3601-03', 3550-52', 3539-41', 3517-19' with (2) 1/2" JHPF. Spot 15% NEFE. Acidize each set of perfs with 500 gals. Frac with 45,500 gals 70 quality foam, 2100# rock salt, (24) 7/8" RCNB's, 49,000# 20/40 sand. Ran BHP. Complete after drilling, perfring, acidizing and fracing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED RD Pate TITLE Area Engineer DATE 3-29-82

APPROVED BY Orig. Signed by Les Clements TITLE Oil & Gas Insp. DATE APR 8 1982

CONDITIONS OF APPROVAL, IF ANY: