

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

JAKE L. HAMON

3. ADDRESS OF OPERATOR

611 Petroleum Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FEL and 1650' FSL, Section 17, T-20-S, R-36-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3609.1' GR

LC-046164 (b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

COM AGR No. SW437

8. FARM OR LEASE NAME

Amerada Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

North Osudo Morrow Gas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 17, T-20-S, R-36-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Commence Operations

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Spudded well @ 12:00 noon, 2/14/81.
2. Drilled 17 1/2" hole to 1365'.
3. Ran 37 jts., 1370.78' of 13 3/8", 8rd, ST&C, 54.5#, K-55 csg, set @ 1365.78' KB.
4. Cemented w/ 1000 sx HOWCO-Lite + 1/4# flocele/sx & 2% CaCl. Followed by 350 sx class "C" + 1/4# flocele/sx & 2% CaCl. Plug down @ 11:10 am, 2/17/81 by Halliburton. Cement circulated.
5. After WOC 20 hrs, NU BOP, pressure tested BOP and surface casing to 1000# for 1/2 hr w/ no pressure loss.
6. Started drilling under surface casing, 2/18/81.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Foreman

DATE 2/20/81

(This space for Federal or State office use)

ACCEPTED FOR RECORD

PETER W. CHESTER

APPROVED BY
CONDITIONS OF APPROVAL

FEB 26 1981

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side