

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

U. S. GEOLOGICAL SURVEY  
P. O. BOX 1100  
HOBBS, NEW MEXICO 88240

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Amoco Production Company
3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, New Mexico 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL x 1980' FEL, Sec. 15  
AT TOP PROD. INTERVAL: (Unit J NW/4, SE/4)  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


5. LEASE  
NM-18237
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Federal BT Gas Com
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Monument Draw Bone Springs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
15-20-35
12. COUNTY OR PARISH  
Lea
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONE ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☒  
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to abandon Wolfcamp and complete in the Bone Springs per the following: Pull tubing, packer, and tailpipe. Run CIBP and set at 11652' cap with 35' class H cement. Log well. Perforate Bone Springs intervals 9192-200, 9320-50, and 9362-72 with 2 JSPF. Go in hole with 2-7/8 tubing and packer. Land tailpipe at 9090' set packer at 9000'. Acidize with 7000 gallons 20% HCL. Run gamma ray temperature survey. Flow or Swab test as necessary.

0+6-USGS, R 1-Hou 1-W. Stafford, Hou 1-DMF 1-Susp

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark L. Luman TITLE Asst. Admin. Analyst DATE 2-12-82

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

FEB 17 1982

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side