

Form 9-331
Dec. 1973

U. N. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL X 1980 FEL, Sec. 15
AT TOP PROD. INTERVAL: (Unit J, NW/4, SE/4)
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☒
☐
☐
☐
☐
☐
☐



OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM 18237
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal BT Gas Com.
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Monument Draw Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
15-20-35
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
30 025 27230
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3717.2 RDB

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in DA&S #193 Service Unit on 6-23-81. Ran 3-5/8" bit in the hole and drilled out cement 13182'-700'. Pulled tubing and bit and ran a gravity correlation log between 13672'-12000. Perforated Morrow at 13566'-582' with 4 JSPF. Ran tailpipe and packer back in hole. Set tailpipe at 13447', packer at 10904'. Acidized with 2500 gal. of 7-1/2% MS acid and 134550 SCF N2. Swabbed 29 hrs. and recovered 41 BW & 6 BL. Moved out service unit. No further report until additional work is evaluated.

0+4-USGS, R 1-Hou 1-Susp 1-MDR 1-Superior, Midland
1-Superior, Woodlands

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark Randolph TITLE Ast. Adm. Analyst DATE 8-21-81

ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY Aug 25 1981 TITLE _____ DATE _____
CONDITIONS OF APPROVAL _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side