

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1980' FEL, Sec. 15
AT TOP PROD. INTERVAL: (Unit J, NW/4, SE/4)
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)		

5. LEASE
NM-18237
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal BT Gas Com.
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Monument Draw Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
15-20-35
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3694.4 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 3-16-81 Kenai Drilling Co. (Rig #23) spudded a 20" hole at 6:00 p.m. Drilled to a TD of 409'. Ran 16" 65# H-40 casing set at 408'. Cemented with 425 SX Class C cement with additives. Plugged down at 6:20 p.m. 3-17-81 and circ. 145 SX. WOC 18 hrs. Tested casing with 1000 PSI for 30 min. Tested OK. Reduced hole to 14-3/4" and resumed drilling.

0+4-USGS, H 1-Hou 1-Susp 1-GLF 1-W. Stafford, Hou
1-Superior, Mid 1-Superior, Woodlands

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Gerald L. Foster TITLE Admin. Analyst DATE 4-16-81APPROVED BY Roger A. Chapman TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APR 22 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side