## Form 9-331 (May 1963)

## COPY TO O. C. (

UNITED STATES DEPARTMEN', F THE INTERIOR

SUBMIT IN	TRIPLI	C.A.	मु•
(Other instr	uctions	ſ	<b>&gt;</b>
verse side)			

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

LC 065658

GEOLOGICAL SURVEY					
SUNDRY	<b>NOTICES</b>	AND	<b>REPORTS</b>	ON	WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

Eunice, New Mexico

LOCATION OF WELL (Report location clearly and in accordance with arrainte require See also space 17 below.)

At surface

_			
7.	UNIT	AGREEMENT	MAME

Teas Yates Unit

8. FARM OR LEASE NAME Y And Teas Yates 🔻 <del>Feder</del>al

9. WELL NO. 1 / SM

15. ELEVATIONS (Show whether DF, RT, GR, Text)

10. PIELD AND POOL, OR WILDCAT

ETeas Capitan Reef

SURVEY OR AREA

SURVEY OR AREA

SORVEY OR AREA

OFF. 10. PIELD AND POOL, OR WILDCAT

ETEAS Capitan Reef

SORVEY OR AREA

S

EIVED

Sec 14 T 20S R 33E

1330' FNL & 1330' FWL

OTHER

Anadarko Production Company

WE'LL GAS WELL

P.O. Box 806

2. NAME OF OPERATOR

16.

14. PERMIT NO.

TES FR SH REL (0

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION 10.	SUBSEQUENT REPORT OF:	
PULL OR ALTER CASING MULTIPLE COMPLETE OOT OR ACIDIZE ABANDON* CHANGE PLANS	WATER SHUT-OFF  FRACTURE TREATMENT SHOOTING OR ACIDIZING  (Other) New Well- Cementing	ASING
ther)	(NOTE: Report results of multiple completion Completion or Recompletion Report and Log fo	on Well

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and somes pertinent to this work.)\*

- Spudded 14-3/4" hole @2:30 A.M. 3-13-81.
   Drilled 14-3/4" hole to 1260'K.B. @11:15 A.M. 3-15-81.
- 3. Ran 1260' of 10-3/4" 40.50# J-55 & K-55 ST&C R-3 w/guide shoe & insert float.
- 4. Cemented w/825 sx Halliburton Light w/ $\frac{1}{4}$ # Flocele per sx & 8# salt per sx. Followed w/200 sx Class C cement w/1# Flocele per sx & 2% CACL. Plug down @7:40 P.M. 3-15-81. Circulated 200 sx cement to pit.
- 5. WOC 18 hrs.
- 6. Test BOP & Csg @1500# psi for 30 min- O.K.

18. I hereby certify that the topegoing is true and correct SIGNED TO	Production-Foreman	March 23,1981
(This space for Federal or State office use)  ACCEPTED FOR RECORD  APPROVED BY PETER W. CHESTER TO CONDITIONS OF APPROVAL, IF ANY:  MAR 2 5 1981	TLE	DATE
U.S. GEOLOGICAL SUR SEE IN ROSWELL, NEW MEXICO	structions on Reverse Side	