

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

Form C-105
Revised 11-1-88

NEW MEXICO OIL CONSERVATION COMMISSION WELL COMPLETION OR RECOMPLETION REPORT AND LOG

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
V-48	

1a. TYPE OF WELL										7. Unit Agreement Name	
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐										-----	
b. TYPE OF COMPLETION										8. Farm or Lease Name	
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☐										State SX	
2. Name of Operator										9. Well No.	
MORRIS R. ANTWEIL										1	
3. Address of Operator										10. Field and Pool, or Wildcat	
P. O. Box 2010, Hobbs, New Mexico 88240										Undesignated	
4. Location of Well										12. County	
UNIT LETTER <u>J</u> LOCATED <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE OF SEC. <u>36</u> TWP. <u>19S</u> RGE. <u>37E</u> NMPM										Lea	
15. Date Spudded		16. Date T.D. Reached		17. Date Compl. (Ready to Prod.)		18. Elevations (DF, RAB, RT, GR, etc.)		19. Elev. Casinghead			
10 April 81		24 April 81		30 November 81		3595' GR		3595'			
20. Total Depth		21. Plug Back T.D.		22. If Multiple Compl., How Many		23. Intervals Drilled By		23. Intervals Rotary Tools			
7150		6800				0-7150		Cable Tools			
24. Producing Interval(s), of this completion - Top, Bottom, Name									25. Was Directional Survey Made		
5774-5926 Paddock									No		
26. Type Electric and Other Logs Run									27. Was Well Cored		
CNL-FDC, DLLO-RXO									No		
28. CASING RECORD (Report all strings set in well)											
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED	
8-5/8"		24#		1500		12-1/4"		750 sx - Circ		None	
4-1/2"		10.5# & 11.6		7150		7-7/8"		675 sx - Top of cmt 3710		None	
29. LINER RECORD										30. TUBING RECORD	
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN		SIZE	
None										2-3/8"	
										5953	
										None	
31. Perforation Record (Interval, size and number)						32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.					
6874, 6876, 6878, 6880, 6882, 6886, 6889, 6890, 6894, 6895, 6900, 6901, 6907, 6908, 6909, 7015, 7016, 7017, 7018 & 7019 (20 holes)						DEPTH INTERVAL					
5774, 5775 1/2, 5777, 5790, 5792, 5796, 5797, 5814, 5815, 5818, 5913, 5915, 5919, 5921, 5925 & 5926 (16 holes)						6874-7019					
						5774-5926					
						5000 gals Acid Plugged back					
						4000 gals Acid, 28000 gals gelled wtr, 33000# sd, 8000 gals 50/50 Acid/CO2					
33. PRODUCTION											
Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)						Well Status (Prod. or Shut-in)			
16 July 81		Pumping 1 1/2" x 2" x 16"						Prod			
Date of Test		Hours Tested		Choke Size		Prod'n. For Test Period		Oil - Bbl.		Gas - MCF	
28 Oct 81		24						6		0	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl.		Gas - MCF		Water - Bbl.	
---		---				6		0		3	
										Oil Gravity - API (Corr.)	
										35.6	
34. Disposition of Gas (Sold, used for fuel, vented, etc.)										Test Witnessed By	
Used for fuel										Parsons	
35. List of Attachments											
Logs, Deviation Record											
36. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.											
SIGNED <u>Jerry Miller</u>						TITLE <u>Agent</u>			DATE <u>1 December 1981</u>		

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs, on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 115.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 1509	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 1597	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____ 2640	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2798	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____ 3001	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ 3623	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4204	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 5413	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____ 5952	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 6506	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____ 6833	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet _____
No. 2, from _____ to _____ feet _____
No. 3, from _____ to _____ feet _____
No. 4, from _____ to _____ feet _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1509	1509	Red Beds				
1509	1597	88	Anhydrite				
1597	2640	1043	Salt w/scattered thin Red Beds				
2640	2798	158	Anhydrite w/thin salt beds				
2798	3001	203	Red Beds				
3001	3850	849	Interbedded Anhydrite & Dolomite, scattered Red Beds				
3850	4710	860	Dolomite				
4710	5040	330	Limestone				
5040	5370	330	Interbedded Limestone Dolomite & Calcareous				
5370	7150	1780	Dolomite				