

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
V-48

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER-

7. Unit Agreement Name

1. Name of Operator

8. Farm or Lease Name
State SX

MORRIS R. ANTWEIL

2. Address of Operator

9. Well No.
1

P. O. Box 2010 Hobbs, New Mexico 88240

3. Location of Well

10. Field and Pool, or Wildcat
Undesignated

UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM

THE East LINE, SECTION 36 TOWNSHIP 19S RANGE 37E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3595' GR

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Completion ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 7150' PBTD 7089' Rigged up well service unit. Tested 4½" casing to 2000 psi - 30 mins - OK. Perforated Drinkard interval with single shots at 6874', 6876', 6878', 6880', 6882', 6886', 6889', 6890', 6894', 6895', 6900', 6901', 6907', 6908', 6909', 7015', 7016', 7017', 7018' & 7019' (20 holes). Ran tubing & packer. Set packer @ 6822'. Treated perfs w/5000 gals. acid. Rate 5.3 b/m w/5930 psi. ISIP 2500 psi, 15-min SIP 2050 psi. Swabbed 20 BW per hour, cut 2% oil. Set bridge plug @ 6820' & capped w/2 sx cement. Prep to perforate Paddock interval.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R M Williams TITLE Agent

DATE 17 Jun 81

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUN 24 1981